



COMFY PLAY®

Document Type: Operating Procedure
Title: ComfyPlay® Installation, Maintenance & Inspection Guidelines
No.: OP24A
Revision Level: 000
Issued by: Eithne Hendricken
Date of Issue: 26/04/2019
Plant: All plants

ComfyPlay® Playground Surfacing Material

Installation, Maintenance & Inspection Guidelines

ComfyPlay® Playground Surfacing Material is an environmentally friendly wood fibre material that conforms with ISEN1176 and ISEN1177 for use as an Impact Attenuating Playground Surfacing Material

Installation:

- 1 Beneath all playground equipment with a free fall height of more than 600mm there shall be impact attenuating surfacing over the entire impact area.
- 2 Ensure that the ground surface is level. If the ground surface is uneven and cannot be levelled, ComfyPlay® must be installed at the minimum depth from the highest point of the ground surface.
- 3 Ensure that the surface is free from sharp edged parts or projections.
- 4 Cover the area with a geotextile membrane before adding ComfyPlay®.
- 5 Spread ComfyPlay® throughout the entire impact area, ensuring the minimum depth is achieved as per Table 1 below.

Maintenance:

- 1 Ensure that the minimum depth as per Table 1 below is maintained at all times.
- 2 ComfyPlay® should be raked back into position after use to ensure that the minimum depth is maintained at all times through the entire impact area and also to avoid excessive compaction of the material.
- 3 ComfyPlay® should be top-dressed on at least an annual basis to compensate for any material breakdown and to ensure that the minimum depth is maintained.
- 4 Keep maintenance records at all times.

Inspection:

- 1 Take regular measurements of the depth of the material at various test positions to ensure that the minimum depth is maintained.
- 2 Ensure that the distance between these test positions is not less than 500mm.
- 3 Keep inspection records at all times.

Table 1:

Material	Description	Minimum depth*	Critical fall height
Woodchip	5 to 30mm grain size	200mm*	≤ 2 metres
		300mm*	≤ 3 metres
*For loose particulate material, add 100mm to the minimum depth to compensate for displacement			

Disclaimer:

ComfyPlay®'s Installation, Maintenance & Inspection Guidelines must be adhered to so as to ensure the effectiveness of this product as an impact attenuating playground surfacing material. CJ Sheeran Limited accept no responsibility for any injuries caused through the incorrect installation, maintenance, inspection or misuse of this product.

The impact attenuating properties of ComfyPlay® may be significantly compromised when in its frozen form and therefore should not be relied on.

